

18V LXT® LITHIUM-ION BRUSHLESS CORDLESS STEEL ROD FLUSH-CUTTER KIT (5.0Ah)



NEW TOOL OVERVIEW XCS06T1

LXT® BRUSHLESS

FEATURES

- Automatic Speed Change™ technology adjusts cutting speed and torque during cut for optimum performance
- Powerful BL™ Brushless Motor delivers 2,200 RPM for faster burr-free cutting
- The BL™ Brushless Motor eliminates carbon brushes, enabling the BL™ Motor to run cooler and more efficiently for longer life
- Stopper holds the rebar at 90° to the cutting blade for faster and more precise cuts
- Spiral bevel gears for smoother rotations and a more efficient transfer of energy
- Rubberized soft grip provides increased comfort on the job

SPECIFICATIONS


Blade Diameter	4-5/16"
Cutting Capacity (thickness)	1"
No Load Speed	2,200 RPM
Lock On Switch	Yes
Lock-Off Switch	No
Switch Type	Slide
Battery	18V LXT® Lithium-Ion
Overall Length	18-17/32"
Net Weight (with battery)	8.8 lbs.
Power Type	Cordless
UPC Code	088381-873529
Shipping Weight	22.93 lbs.



3
YEAR
WARRANTY
LITHIUM-ION
TOOL &
BATTERY

ALSO AVAILABLE AS A BARE TOOL: XCS06ZK

PRODUCT HIGHLIGHTS



CAPACITY

Effortless cutting of up to #8 rebar or 1" threaded rod; cuts up to an 1/8" flush to the surface




ERGONOMICS

Three position adjustable side handle for operator comfort and convenience



APPLICATIONS

Carbide-tipped blade delivers clean burr-free cutting with minimal spark emission



CONVENIENCE

Chip collecting bag captures metal cut-offs (optional accessory)

STANDARD EQUIPMENT

- 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)
- 18V LXT® Lithium-Ion Rapid Optimum Charger (DC18RC)
- 4-5/16" 24T Carbide-Tipped Blade (SC09003261)
- Hex Wrench (M5) (SC08200100)
- Side Handle
- Tool Case

RELATED PRODUCTS

1. Chip Collector (SC08106610)
2. 18V LXT® Lithium-Ion 6.0Ah Battery (BL1860B)
3. 18V LXT® Brushless Rebar Tying Tool Kit (XRT01TK)
4. 18V LXT® BL™ 5-7/8" Metal Cutting Saw Kit, w/ Electric Brake
5. and Chip Collector (XSC04T)
6. 18V LXT® Brushless 4-1/2" / 5" Cut-Off/Angle Grinder Kit (XAG11T)

1



2



3



4



5

