

12V max CXT[®] LITHIUM-ION BRUSHLESS CORDLESS 3/8" SQ. DRIVE IMPACT WRENCH KIT (2.0Ah)



NEW TOOL OVERVIEW WT05R1

CXT[®] BRUSHLESS

FEATURES

- BL™ Brushless Motor delivers 120 ft.lbs. of Max Torque and 210 ft.lbs. of Nut-Busting Torque
- Variable 2-speed (0-1,300/0-2,400 RPM & 0-2,000/0-3,600 IPM) for a wide range of fastening applications
- Reverse Rotation Auto-Stop Mode stops rotation and impact when fastener is loosened adequately
- Ultra-compact design at only 5-5/8"
- Weighs only 2.2 lbs. with battery for reduced operator fatigue
- Built-in L.E.D. light illuminates the work area
- Ergonomically designed handle with rubberized soft grip provides increased comfort
- Ideal for working in tight spaces and overhead applications

SPECIFICATIONS


Square Drive	3/8"
No Load Speed (var. 2 spd)	0 - 1,300 / 0 - 2,400 RPM
Impacts Per Minute (var. 2 spd.)	0 - 2,000 / 0 - 3,600 IPM
Maximum Torque (ft.lbs./N•m)	120 ft.lbs./160 N•m
Nut-Busting Torque (ft.lbs./N•m)	210 ft.lbs./290 N•m
Battery	12V max CXT™ Lithium-Ion
Overall Length	5-5/8"
Net Weight (with battery)	2.2 lbs.
UPC Code	088381876926 (WT05R1)
UPC Code	088381-876797 (WT05Z)



ALSO AVAILABLE AS A BARE TOOL: WT05Z



PRODUCT HIGHLIGHTS



CONVENIENCE

3/8" square drive fits most common automotive sockets



COMFORT

Ultra-compact design at only 5-5/8" long and weighs only 2.2 lbs. for reduced fatigue



POWER

BL™ Brushless Motor delivers 120 ft.lbs. of Max Torque and 210 ft.lbs. of Nut-Busting Torque



SPEED

Variable 2-speed (0-1,300/0-2,400 RPM & 0-2,000/0-3,600 IPM) for a variety of fastening applications

STANDARD EQUIPMENT

- (2) 12V max CXT™ Lithium-Ion 2.0Ah Battery (BL1021B)
- 12V max CXT™ Lithium-Ion Charger (DC10WD)
- Tool bag

RELATED PRODUCTS

1. 12V max CXT™ Lithium-Ion 4.0Ah Battery (BL1041B)
2. 12V max CXT™ Lithium-Ion Rapid Optimum Charger (DC10SB)
3. Impact GOLD[®] 9Pc 3/8" Metric Sckt St w/15° Tilt Ad (B-49862)
4. 14 Pc. 3/8" Drive Deep Well Impact Socket Set (A-99655)
5. 12V max CXT™ Adjustable Beam L.E.D. Flashlight (ML106)

