

# 18V X2 LXT® LITHIUM-ION CORDLESS UPRIGHT L.E.D. AREA LIGHT, LIGHT ONLY



## NEW TOOL OVERVIEW DML810

**LXT® X2 18V + 18V 36V**

### FEATURES

- Self-righting design keeps work light in upright position
- Battery or corded operation; compatible with 18V LXT® batteries (batteries and charger not included)
- Up to 3.3 hours of continuous illumination with two 5.0Ah 18V LXT® battery on high (batteries and charger not included)
- Up to 15 hours of continuous illumination with two 5.0Ah 18V LXT® battery on low (batteries and charger not included)
- Holds (2) 18V LXT® Lithium-Ion batteries but operates using (1) 18V battery at a time; utilizes second battery when needed
- Back up power is provided by an 18V LXT® battery and keeps the flood light on if AC power is lost (charged battery must be installed)
- L.E.D. lights effectively illuminate work area without the high heat of halogens and incandescent lights
- Convenient carrying handles for easy handling

### SPECIFICATIONS

|   |                               |
|---|-------------------------------|
| <b>Voltage</b> .....                      | 18V                           |
| <b>Battery</b> .....                      | 18V LXT® Lithium-Ion          |
| <b>Cordless/Corded</b> .....              | Corded and Cordless Operation |
| <b>AC Adapter Included</b> .....          | Yes                           |
| <b>Lumens (high/med/low)</b> .....        | 5,500 / 3,000 / 1,500 lm      |
| <b>Run Time (high/med/low)</b> .....      | 3.3 / 7 / 15 hrs              |
| <b>Run Time (max. in minutes)</b> .....   | 18                            |
| <b>Dimensions (LxWxH)</b> .....           | 16-1/2" x 16-1/2" x 31"       |
| <b>Net Weight (without battery)</b> ..... | 30.6 lbs.                     |
| <b>Shipping Weight</b> .....              | 39.8 lbs.                     |
| <b>UPC Code</b> .....                     | 088381-891103                 |

### STANDARD EQUIPMENT

- 18V X2 LXT® Upright L.E.D. Area Light, Light Only (DML810)
- AC Power Cord



### PRODUCT HIGHLIGHTS



#### CONTROL

3-mode operation: delivers 5,500 lumens on High, 3,000 lumens on medium, and 1,500 lumens on Low




#### PRODUCTIVITY

AC inlet and outlet can be used to chain multiple upright lights together



#### VERSATILITY

3 illumination range modes: 360°, left 180°, and right 180°



#### DURABILITY

Dust / water-resistant construction (IP54 rated) for improved operation in harsh job site conditions

### RELATED PRODUCTS

1. 18V X2 LXT® Cordless/Corded Work Light (DML809)
2. 18V LXT® Cordless/Corded Work Light (DML811)
3. 18V LXT® L.E.D. Flashlight / Spotlight (DML812)
4. 18V LXT® Lithium-Ion 6.0Ah Battery (BL1860B)
5. 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B)

