



Supplies:

- 1 package 10" squares
- 1 package Bosal In-R-Form Sew In Foam Stabilizer
- 1/4 yard Heat N Bond Fusible Interfacing Light Weight Fusible
- 12" length of boning
- 3" length of 1/2" Velcro

Cut:

- Main fabric** (4) 10" x 8" rectangles
- Pocket fabric** (2) 10" x 4 3/4" rectangles
- Accent fabric** (8) 1 3/4" x 8" rectangles
(4) 1 3/4" x 4 3/4" rectangles
- Bosal Foam** (2) 7 1/4" x 12" rectangles
(3) 1 3/4" x 4" rectangles
- Boning** 12" length
- Interfacing** (1) 4 3/4" x 12 1/2" rectangles
- 1/2" wide Velcro** (1) 3" length

Pincushion Construction:

Stack the (3) 1 3/4" x 4" rectangles of Bosal foam and sew them together along the perimeter. Insert this foam cushion into the 2" pocket.

Thread Catcher

Use (1) 10" square.

- 1: Cut (2) 10" x 5" rectangles from square.
- 2: Place Velcro 1" over and 3/4" down from top of raw edge.
- 3: Fold right sides together to 5" x 5". Sew up from corners.
- 4: Set liner in bag, right sides together. Sew 75% close, leaving a space open at velcro.

