



Intelligent Battery Management System

| | | |
|---|---|---|
|  Temperature Protection |  Over-Voltage Protection |  Over-Current Protection |
|  Heating Film |  Parallel & Serial Balancing Strategy |  Short-circuit Protection |

KEY FEATURES

Ultra-Safety

The battery management system (BMS) provides comprehensive protection to the battery and manages the charging/discharging process wisely.

Auto-Balance

Connects multiple batteries in parallel safely without internal state non-uniformity issues.

Uncompromising Quality

State-of-the-art battery cells ensure a lifespan of more than 6000 cycles, 100A continuous discharge current, and a wide range of operation temperature.

Communication

CAN, RS485, Blue Tooth, Dry Contact enable data transmission to meet the needs of different usage scenarios.

12V Series

All Purpose Lithium Ion Batteries



SPECIFICATION

| Model | RT12100G31 |
|---|-----------------------------|
| Electrical | |
| Nominal Voltage(V) | 12.8 |
| Nominal Capacity(Ah) | 100 |
| Working Voltage Range(VDC) | 10.8~14.4 |
| Internal Resistance(mΩ) | <20 |
| Charge Voltage(VDC) | 14V-14.4 |
| Nominal Operation Current(A) | 20 |
| Max. continuous operation current(A) | 100 |
| Peak Current(A) | 200A@30sec |
| Serial Connection | 1 - 4 pcs |
| Parallel Connection | 1S≤16P, 2S≤8P, 3S≤5P, 4S≤4P |
| Structure | |
| Dimension (mm) | 325*173.5*226 |
| Weight(Kg) | 13kg±0.2 |
| IP rating | IP67 |
| Power Terminal | M8 bolt |
| Working Environment | |
| Charge working temperature (C) | 0~60 |
| Discharge working temperature (C) | -20~60 |
| Working temperature (C) | -40~60 |
| Altitude (M) | <4,000 |
| Humidity(RH) | 5~95% (w/o condensing) |
| Communication | |
| RS485 | 115200bps |
| CAN | 500Kbps |
| Bluetooth | BLE5.0 |
| Dry contactor | 2×inputs & 2×outputs |
| Certification | |
| SAE J930, SAE J1455, UL1973, IEC62619,FCC,CE, Bluetooth SIG, UN38.3 | |

*During -40 C ~ -20 C , only heater will be enabled for heating up the module, battery cannot charge/discharge during such period.

