

SPECIFICATION

PRODUCT SPECIFICATION:	CAT5E FTP 26AWG	 <div style="display: flex; justify-content: flex-end; margin-top: 10px;"> <ul style="list-style-type: none"> 导体 Conductor 对绞线对 Twisted pairs 绝缘Insulation 聚脂带PET 铝箔AL 地线Drain Wire 外被Jacket </div>
Construction		
Conductor	Bare Copper	
4 Twisted Pair	8C	
AWG	26AWG	
Construction (MM) (±0.01)	7/0.16	
Stranded Dia. (MM)	0.48	
Insulation	PE	
Nom. Thickness (MM)	0.18	
Insulation Dia. (±0.05)	0.88	
Darin wire(±0.01)	7/0.16TC	NEXT 4-100MHz IEC61156-6:EQUATION(6), CONSTANT VALUES SEE TABLE CAT. 5E
Shield/Braid	/	PS NEXT 4-100MHz IEC61156-6:EQUATION(5), CONSTANT VALUES SEE TABLE CAT. 5E
Jacket	PVC	ELFEXT 4-100MHz IEC61156-6:EQUATION(7), CONSTANT VALUES SEE TABLE 6CAT. 5E
Nom. Thickness ±0.1MM	0.6	PS ELFEXT 4-100MHz IEC61156-6:EQUATION(7), CONSTANT VALUES SEE TABLE CAT. 5E
Outer Dia. (±0.2MM)	6.0	
Insulation	Jacket Marking: (White font) E348815 C(UL)US CMX OUTDOOR-CMR 75°C FTP 4PR 26AWG	
Cores:Pairs		
P1:Blue & BU/White	P2:Orange &OR/ White	
P3:Green &GN/ White	P4:Brown &BO/ White	